



CHEMEX



Fluorosynthetic Foam AFFF

● PHYSICAL DATA

	CHEMEX		
	1	3	6
Appearance /colour	Light yellow liquid		
Concentration of use	1 %	3 %	6 %
Specific Gravity at 20°C (Kg/dm3)	1.03	1.02	1.01
Viscosity at 20°C (cStokes)	15	5	2
Freezing point	-21°C	-10°C	-5°C
Ph at 20°C	8		
Sediments after ageing	0 %		
Surface tension (mN/m)	19		
Interfacial tension (mN/m)	2		

● FOAM QUALITY

Low Expansion	8
Drainage Time 25% / 50%	2 min. / 4 min.
Medium Expansion	100

Foam Expansion values depend on the equipment

● PERFORMANCE & WARRANTY

CHEMEX meets international requirements
EN 1568-3: Class IIIC
Marine: BV

CHEMEX can be used with tap and sea water.

CHEMEX can be premixed for sprinklers, bladder tanks...

CHEMEX has a 10 years warranty in its original packaging and at storage temperatures 0°C / +60°C.



No: FM 560021

Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

www.3fff.co.uk