

## High Pressure Fire Attack System Diesel Engine

### SPECIFICATIONS & WARRANTY

|                  |   |
|------------------|---|
| Body and frame   | Stainless Steel Grade 304                           |
| Pump             | 19 l/mn – 5 GPM                                     |
| Maximum pressure | 185 Bars - 2800 psi                                 |
| Engine           | 10.9 HP – 8.0 Kw Lombardini                         |
| Diesel Tank      | 5 liters<br>2 hours runtime at maximum speed        |
| Battery          | 12V -30A/h Dry-cell sealed, 12 months load          |
| Starter          | 12 volt electric key or Manual recoil               |
| Hoses            | 2 hoses reel, length 2 x 30 m - extendable to 120 m |
| Weight           | 110 Kg  |
| Dimensions       | LxWxH 90x60x60                                      |
| Guarantee        | 1 Year  |

### DESCRIPTION

- Compact and lightweight **portable** system
- Working pressure up to 185 Bars – 2800 psi –
- Extension up to 120 meters hose length with no pressure loss
- Can be installed with our water tank or vehicle tank
- 4 Ergonomic handles to lift from all sides
- Stainless steel frames for longevity
- Easy training, intuitive use
- Discharge: Twin hose reels x 30 m, equipped with 2 twin lances for jet/spray / low/high pressure / foam
- Fast Connection type Safety Lock Guyson Fitting
- Water connection type Storz

### OPERATING CONTROLS

*Controls are easy to operate and include:*

- Engine electric key start / stop
- Automatic throttle control
- Hour meter, Tachometer
- Pump pressure gauge
- Emergency Stop



No: FM 560021

Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,  
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

[www.3fff.co.uk](http://www.3fff.co.uk)