

Fire Angel

3F

High Pressure Fire Attack System Petrol Engine

SPECIFICATIONS & WARRANTY

FIRE ANGEL	202	202F	301	301F	302	302F
Body and Frame	Steel frame with epoxy black coating					
Pump	Speck Triple ceramic pistons and body in brass					
Flow rate	20 l/mn – 5 GPM					
Maximum pressure	180 Bars - 2800 psi					
Engine	13 CV– 8.2 Kw Honda – 4 tiempos					
Petrol tank	6 litres • 1.5 hour runtime at maximum speed					
Battery	12V -13A/h Dry-cell sealed, 12 months load					
Starter	12 Volt electric key or Manual recoil					
Reel	2	2	1	1	2	2
Hose	20 m	20 m	30 m	30 m	30 m	30 m
Weight	99 kg	103 kg	95 kg	97 kg	110 kg	114 kg
Dimensions	90x60x66 (LxWxH)					
Warranty	1 year					

DESCRIPTION

- Compact and Lightweight portable system
- Working Pressure up to 180 Bar – 2800 psi
- Extension up to 120 meters hose length with no pressure loss
- Can be installed with our water tank or vehicle tank
- Steel frame with epoxy coating
- Easy training, intuitive use
- Discharge: 1 or 2 hose reels x 20 m or 30 m,
 - Fire Angel 202•301•302 : equipped with 1 or 2 lances for jet-spray / low-high pressure for water
 - Fire Angel 202F•301F•302F : equipped with 1 or 2 lances for jet-spray / low-high pressure for water/foam
- Fast connection type Safety Lock Guyson Fitting
- Water tank with Storz coupling

OPERATING CONTROLS

Controls are easy to operate and include:

- Electrical starter with key ON/OFF
- Automatic choke control
- LCD display with running time / Engine rev.
- Pressure gauge
- Emergency button
- Model F: Foam dosing system



No: FM 560021

Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

www.3fff.co.uk