



FILMEX



Fluorosynthetic Foam AFF-AR

PERFORMANCE & WARRANTY

FILMEX meets international requirements
EN 1568-3: Class IA
EN 1568-4: Class IA
ISO 7203-1, 3
NATO Listed
Marine: BV

FILMEX can be used with tap and sea water.

FILMEX can be used for sprinklers, bladder tanks...

FILMEX has a 10 years warranty in its original packaging and at storage temperatures -30°C / +60°C

PHYSICAL DATA

	FILMEX		
	1x3	3x3	3x6
Appearance /colour	Yellow gel		
Concentration of use on Hydrocarbons	1 %	3 %	3 %
Concentration of use on Solvents	3 %	3 %	6 %
Specific Gravity at 20°C (Kg/dm ³)	1.05	1.04	1.03
Viscosity at 20°C (mPa.s)	1600	1400	1200
Freezing point	-17°C	-15°C	-12°C
Ph at 20°C	7		
Sediments after ageing	< 0.1 %		
Surface tension (mN/m)	20		
Interfacial tension (mN/m)	3		

FOAM QUALITY

Low Expansion	8
Drainage Time 25% / 50%	8 min. / 15 min.
Medium Expansion	50
High Expansion	400

Foam Expansion values depend on the equipment



Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

No: FM 560021

www.3fff.co.uk