



FLUOEX



Fluorosynthetic Foam AFFF

PHYSICAL DATA

Appearance /colour
 Concentration of use
 Specific Gravity at 20°C (Kg/dm3)
 Viscosity at 20°C (cStokes)
 Freezing point
 Ph at 20°C
 Sediments after ageing
 Surface tension (mN/m)
 Interfacial tension (mN/m)

FLUOEX

	1	3	6
	Light yellow liquid		
	1 %	3 %	6 %
	1.03	1.02	1.01
	10	4	4
	-20°C	-5°C	-3°C
	8		
	0 %		
	17		
	3		

PERFORMANCE & WARRANTY

FLUOEX meets international requirements
 EN 1568-3: Class IC
 ISO 7203-1
 Marine: BV

- FLUOEX can be used with tap and sea water.
- FLUOEX can be premixed for sprinklers, bladder tanks...
- FLUOEX is compatible with usage of dry powder.
- FLUOEX has a 10 years warranty in its original packaging and at storage temperatures -30°C / +60°C

FOAM QUALITY

Low Expansion
 Drainage Time 25% / 50%
 Medium Expansion

	8
	2 min. / 4 min.
	100

Foam Expansion values depend on the equipment



Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk
 Unit B, 18 Brunel Road, Earlstree Industrial Estate,
 Corby, Northants, NN17 4JW, United Kingdom
 V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

www.3fff.co.uk