



# FLUOEX



## Fluorosynthetic Foam AFFF

### PHYSICAL DATA

Appearance /colour  
 Concentration of use  
 Specific Gravity at 20°C (Kg/dm3)  
 Viscosity at 20°C (cStokes)  
 Freezing point  
 Ph at 20°C  
 Sediments after ageing  
 Surface tension (mN/m)  
 Interfacial tension (mN/m)

### FLUOEX

	1	3	6
	Light yellow liquid		
	1 %	3 %	6 %
	1.01	1.01	1.00
	10	4	4
	-20°C	-5°C	-3°C

### PERFORMANCE & WARRANTY

FLUOEX meets international requirements  
 EN 1568-3: Class IC  
 ISO 7203-1  
 Marine: BV

FLUOEX can be used with tap and sea water.

FLUOEX can be premixed for sprinklers, bladder tanks...

FLUOEX is compatible with usage of dry powder.

FLUOEX has a 10 years warranty in its original packaging  
 and at storage temperatures -30°C / +60°C

### FOAM QUALITY

Low Expansion  
 Drainage Time 25% / 50%  
 Medium Expansion

9  
 3 min. / 5 min.  
 50

*Foam Expansion values depend on the equipment*



Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk  
 Unit B, 18 Brunel Road, Earlstree Industrial Estate,  
 Corby, Northants, NN17 4JW, United Kingdom  
 V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

[www.3fff.co.uk](http://www.3fff.co.uk)