

# FREEDEX SF5 3F

SF

## Class A & B Extinguisher Additive Fluorine Free Solvent Free

### ● PERFORMANCE & WARRANTY

FREEDEX SF5 meets AS/NZ 1850:2009 as an extinguisher additive. Typical rating for a 9 liters extinguisher is 4A/20B.

FREEDEX SF5 must be used as a ready to use additive 100% active matter.

FREEDEX SF5 has a 5 years warranty in its original packaging at storage temperatures 0°C / +60°C, and when contained in a lined extinguisher.

### ● PHYSICAL DATA

	FREEDEX SF5 <b>SF</b>
Colour	Off-white
Specific Gravity at 20°C (Kg/dm <sup>3</sup> )	1.00
Viscosity at 20°C (cStokes)	150
Freezing point	-3°C
Ph at 20°C	7
Low expansion 100%	6
Medium expansion	80
Drainage time 50%	>1 hour

### ● EXTINGUISHER - Typical rating AS/NZ 1850:2009

9 litre	4A / 20B
---------	----------



No: FM 560021

Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,  
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

[www.3fff.co.uk](http://www.3fff.co.uk)