

FREEDOL SF **3F**

Synthetic Foam Concentrate **FFF AR** **Fluorine Free** **Solvent Free**

● PERFORMANCE & WARRANTY

FREEDOL SF meets international requirements

EN1568-1 & 2: Pass
EN1568-3: Class III C
EN1568-4: Class IC
ICAO Level B
Marine: BV

FREEDOL SF can be used with tap and sea water

FREEDOL SF has a 10 years warranty in its original packaging and at storage temperatures -30°C / +60°C.

● PHYSICAL DATA

Appearance / colour	Green Gel
Concentration of use on Hydrocarbons	3 %
Concentration of use on Solvents	3 %
Specific gravity at 20°C (Kg/dm ³)	1.01
Viscosity at 20°C (mPa.s)	2000
Ph at 20°C	7
Freezing point	-13°C
Sediment after ageing	0 %
Surface tension at 3% (mN/m)	25

● FOAM QUALITY AT 3%

Low expansion	7
Drainage time 25% / 50%	10 min / 15 min
Medium expansion	50
High expansion	500

Foam Expansion value depends on the equipment



No: FM 560021

Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

www.3fff.co.uk