

FREEDOL

3F

Synthetic Foam Concentrate FFF AR Fluorine Free

PERFORMANCE & WARRANTY

FREEDOL meets international requirements
EN1568-1 & 2: Pass
EN1568-3: Class IIIC (3%)
EN1568-4: Class IIC (3%) Class IA (6%)
ISO 7203-1, 2, 3
Marine: BV
LASTFIRE TEST – Hydrocarbon, Ethanol
ICAO Level B
NATO Listed
APSAD T12

FREEDOL can be used with tap and sea water

FREEDOL has a 10 years warranty in its original packaging and at storage temperatures -30°C / +60°C.

PHYSICAL DATA

Appearance / colour	Green Gel
Concentration of use on Hydrocarbons	3 %
Concentration of use on Solvents	3 or 6 %
Specific gravity at 20°C (Kg/dm ³)	1.06
Viscosity at 20°C (mPa.s)	1300
Ph at 20°C	7
Freezing point	-16°C
Sediment after ageing	< 0.1%
Surface tension at 3% (mN/m)	25

FOAM QUALITY

Concentration of use	3 %	6%
Low expansion	8	9
Drainage time 25%	15 min.	30 min.
Medium expansion	60	130
High expansion	800	900

Foam Expansion value depends on the equipment



No: FM 560021

Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

www.3fff.co.uk