



FREEFOR



Wetting and Foaming Agent Fluorine Free

PHYSICAL DATA

	15	21	63
Appearance /colour		Light red liquid	
Concentration for wetting application	0.1-0.3%	0.1-0.5%	0.1-1%
Concentration for foaming application	0.3-0.5%	0.5-1%	1-3%
Specific Gravity at 20°C (Kg/dm ³)	1.03	1.02	1.01
Viscosity at 20°C (cStokes)	25	10	5
Freezing point	-14°C	-10°C	-5°C
Ph at 20°C		7	
Sediments after ageing		0 %	
Surface tension (mN/m)		25	

FREEFOR

PERFORMANCE & WARRANTY

FREEFOR meets international requirements

EN 1568-1 & 2: Pass

EN 1568-3: Class IIIC

Marine: BV

FREEFOR can be used for all structural fires with tap water, sea water and brackish water.

FREEFOR has a 10 years warranty in its original packaging and at storage temperatures -30°C / +60°C.

FOAM QUALITY

Low Expansion

10

Drainage Time 25% / 50%

7 min. / 12 min.

Medium Expansion

100

High Expansion

800

Foam Expansion values depend on the equipment



No: FM 560021

Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

www.3fff.co.uk