



# FREEFOR



## Wetting and Foaming Agent Fluorine Free

### PERFORMANCE & WARRANTY

FREEFOR meets international requirements  
EN 1568-1 & 2: Pass  
EN 1568-3: Class IIIC  
Marine: BV

FREEFOR can be used for all structural fires with tap water, sea water and brackish water.

FREEFOR has a 10 years warranty in its original packaging and at storage temperatures -30°C / +60°C.

### PHYSICAL DATA

	15	21	63
Appearance /colour		Light red liquid	
Concentration for wetting application	0.1-0.3%	0.1-0.5%	0.1-1%
Concentration for foaming application	0.3-0.5%	0.5-1%	1-3%
Specific Gravity at 20°C (Kg/dm3)	1.03	1.02	1.00
Viscosity at 20°C (cStokes)	35	10	5
Freezing point	-14°C	-10°C	-5°C
Ph at 20°C		7	
Sediments after ageing		0 %	
Surface tension (mN/m)		25	

### FOAM QUALITY

Low Expansion	10
Drainage Time 25% / 50%	7 min. / 12 min.
Medium Expansion	100
High Expansion	800

*Foam Expansion values depend on the equipment*



Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk  
Unit B, 18 Brunel Road, Earlstree Industrial Estate,  
Corby, Northants, NN17 4JW, United Kingdom  
V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

[www.3fff.co.uk](http://www.3fff.co.uk)