

FREEGEN SF-LV **3F**

SF

Synthetic Foam Concentrate FFF AR 3x3 Fluorine Free Solvent Free

● PHYSICAL DATA

| | |
|--------------------------------------|-----------|
| Appearance /colour | off-white |
| Concentration of use on Hydrocarbons | 3 % |
| Concentration of use on Solvents | 3 % |
| Concentration of use on Solids | 1% |
| Specific Gravity at 20°C (Kg/dm3) | 1.05 |
| Viscosity at 20°C (mPa.s) | 900 |
| Ph at 20°C | 7 |
| Freezing point | -8°C |
| Sediments after ageing | 0 % |
| Surface tension at 3% (mN/m) | 25 |

FREEGEN SF-LV **SF**

● PERFORMANCE & WARRANTY

FREEGEN SF-LV meets international standards

EN 1568-1 & 2: Pass

EN 1568-3: Class 1-A

EN 1568-4: Class 1A (Acetone) - 1B (Isopropanol)

ICAO Level B

LASTFIRE

FREEGEN SF-LV can be used with tap and sea water.

FREEGEN SF-LV can be used for training at between 0.5 and 1.0

FREEGEN SF-LV can be used with all known equipment on the market.

FREEGEN SF-LV has a 10 years warranty in its original packaging and at storage temperatures -30°C / +60°C.

● FOAM QUALITY AT 3%

| | |
|-------------------------|---------------------|
| Low Expansion | 7 |
| Drainage Time 25% / 50% | > 30 min / > 60 min |
| Medium expansion | 80 |
| High expansion | 400 |



No: FM 560021

Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

www.3fff.co.uk