

# FREEGEN SF-LV **3F**

**SF**

## Synthetic Foam Concentrate FFF AR 3x3 Fluorine Free Solvent Free

### PERFORMANCE & WARRANTY

FREEGEN SF-LV meets international standards

EN 1568-1 & 2: Pass

EN 1568-3: Class 1-A

EN 1568-4: Class 1A (Acetone) - 1B (Isopropanol)

ICAO Level B

LASTFIRE

FREEGEN SF-LV can be used with tap and sea water.

FREEGEN SF-LV can be used with all known equipment on the market.

FREEGEN SF-LV has a 10 years warranty in its original packaging and at storage temperatures -30°C / +60°C.

### PHYSICAL DATA

Appearance /colour	off-white
Concentration of use on Hydrocarbons	3 %
Concentration of use on Solvents	3 %
Specific Gravity at 20°C (Kg/dm3)	1.05
Viscosity at 20°C (mPa.s)	900
Ph at 20°C	7
Freezing point	-8°C
Sediments after ageing	0 %
Surface tension at 3% (mN/m)	25

### FOAM QUALITY AT 3%

Low Expansion	7
Drainage Time 25% / 50%	> 30 min / > 60 min
Medium expansion	80
High expansion	400

Foam Expansion values depend on the equipment

### FREEGEN SF-LV **SF**



No: FM 560021

Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,  
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

[www.3fff.co.uk](http://www.3fff.co.uk)