



FREEGEN



Synthetic Foam Concentrate FFF AR 3x3 Fluorine Free

● PERFORMANCE & WARRANTY

FREEGEN meets international standards

EN1568-1 & 2: Pass
EN1568-3: Class 1-A
EN1568-4: Class 1A - 1A
ICAO Level B
LASTFIRE

FREEGEN can be used with tap and sea water

FREEGEN can be used with all known equipment on the market

FREEGEN has a 10 years warranty in its original packaging and at storage temperatures -30°C / +60°C.

● PHYSICAL DATA

	FREEGEN
Appearance / colour	off-white
Concentration of use on Hydrocarbons	3 %
Concentration of use on Solvents	3 %
Specific gravity at 20°C (Kg/dm ³)	1.04
Viscosity at 20°C (mPa.s)	1500
Ph at 20°C	7,5
Freezing point	-7°C
Sediment after ageing	0 %
Surface tension at 3% (mN/m)	24

● FOAM QUALITY AT 3%

Low expansion	7
Drainage time 25% / 50%	> 30 min / > 60 min
Medium expansion	40
High expansion	400

Foam Expansion value depends on the equipment



No: FM 560021

Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

www.3fff.co.uk