

# FREESOLV SF



SF

## Fluorosynthetic Foam AFFF Solvent Free

### PERFORMANCE & WARRANTY

FREESOLV SF meets international requirements  
EN 1568-3: Class IC  
LASTFIRE TEST: Hydrocarbons  
ISO 7203-1  
ICAO Level B  
NATO Listed  
Marine: BV

FREESOLV SF can be used with tap and sea water.

FREESOLV SF can be premixed for sprinklers, bladder tanks...

FREESOLV SF is compatible with usage of dry powder.

FREESOLV SF has a 10 years warranty in its original packaging and at storage temperatures -30°C / +60°C

### PHYSICAL DATA

Appearance /colour

Concentration of use

Specific Gravity at 20°C (Kg/dm<sup>3</sup>)

Viscosity at 20°C (cStokes)

Freezing point

Ph at 20°C

Sediments after ageing

Surface tension (mN/m)

Interfacial tension (mN/m)

### FOAM QUALITY

Low Expansion

Drainage Time 25% / 50%

Medium Expansion

*Foam Expansion values depend on the equipment*

### FREESOLV SF

1 SF 3 SF 6 SF

Light yellow liquid

1 % 3 % 6 %

1.02 1.01 1.00

12 8 4

-12°C -8°C -5°C

8

< 0.1 %

16

2

8

3 min. / 5 min.

40



No: FM 560021

Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,  
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

[www.3fff.co.uk](http://www.3fff.co.uk)