



# FREEZOL



## Anti-Freeze

### ● PERFORMANCE & WARRANTY

FREEZOL is a blend of selected anti-freeze agents. FREEZOL is specifically designed as an additive for extinguishers. It was conceived to combine high freeze protection and good hydrophilic balance to prevent any lowering in extinguishing performance. FREEZOL offers a long-lasting stability after mixing in water (with AFFF or other synthetic foams). FREEZOL is chemically inert and does not react with the liquid additives for A and B class. FREEZOL does not contain ethylene glycol.

FREEZOL has a 2 years warranty in its original packaging and at storage temperatures -30°C / +40°C.

FREEZOL is moisture sensitive and absorbs air humidity. It is recommended to use the product in the 3 months after opening.

### ● PHYSICAL DATA

Appearance / Colour	Green liquid
Specific Gravity at 20°C	1.12
Viscosity at 20°C	200
Ph at 20°C	7
Freezing point	< - 30°C
Flash Point	> 103°C
Boiling Point	> 190°C
Solubility	Soluble in all proportions in water

### ● TEMPERATURE

	FREEZOL CONTENT % (with water)	FREEZOL CONTENT % (with AFFF)
- 5°C	5%	0%
- 10°C	20%	5%
- 15°C	25%	25%
- 20°C	35%	35%
- 25°C	40%	40%
- 30°C	50%	50%

*We recommend to use A1170 foam booster to maintain AFFF solution properties.*



Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate, Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

No: FM 560021

[www.3fff.co.uk](http://www.3fff.co.uk)