

# 3F



# FREESOLV SF

## Fluorosynthetic Foam AFFF

Solvent free

### PHYSICAL DATA ●

	SF FREESOLV SF		
	1	3	6
Appearance / colour	Light yellow liquid		
Concentration of use	1%	3%	6%
Specific gravity at 20°C (Kg/dm <sup>3</sup> )	1.02	1.01	1.00
Viscosity at 20°C (cStokes)	12	8	4
Freezing point	-12°C	-8°C	-5°C
pH at 20°C	8		
Sediments after ageing	< 0.1%		
Surface tension (mN/m)	16		
Interfacial tension (mN/m)	2		

### FOAM QUALITY ●

Low Expansion	8
Drainage Time 25% / 50%	3 min. / 5 min.
Medium Expansion	40

Foam Expansion value depends on the equipment

SF: Smart Foam



### PERFORMANCE & WARRANTY ●

FREESOLV SF meets international requirements  
EN 1568-3: Class IB  
LASTFIRE TEST: Hydrocarbons  
ISO 7203-1  
ICAO Level B  
NATO Listed  
Marine: IMO

FREESOLV SF can be used with tap and sea water.

FREESOLV SF can be premixed for sprinklers, bladder tanks...

FREESOLV SF is compatible with usage of dry powder.

FREESOLV SF has a 10 years warranty in its original packaging and at storage temperatures -30°C / +60°C