



FAS CAFS

Portable Back pack Foam Extinguishing System

DESCRIPTION ●

	FAS CAF G10	FAS CAF SF10
Volume	10 litres	
Operating Pressure	18 bars	
Flow rate	13,33 litre/min Wet 5,21 litre/min Dry	
Operating temperature	0°C à 60°C	
Distance of throw	16 metres Wet 11 metres Dry	
Foam agent	GENEX ESC @3% by volume	FREDEX SF1 @100%
Frost protection	-10°C (FREEZOL @10%)	-5°C
Electrical test	EN3 – to 1,000 Volt / 2 metres distance	
Propellant	Air supplied by 300 bar cylinder (2 litre)	
Rating	55A – 233B 43A – 183B (-10°C)	34A – 183B
Weight	12,5 kg empty – 28,8 kg filled	
Dimension	570 mm High – 220 mm Diameter	
Cylinder	CE 0036	



PERFORMANCE ●

High Performance for professional fire-fighters

This new addition to the FAS family of fire-fighting equipment from 3F combines quality, functionality and effectiveness for rapid and secure fire extinction. The unique high performance of the FAS CAFS is based on the alternate production of easy flowing wet foam or long lasting and sticky light foam providing rapid extinguishing with exceptional burn-back resistance.

FAS CAFS SF10 is eco-friendly and safe for the environment: it is FLUORO-FREE and SOLVENT-FREE thanks to our unique technology Smart Foams®

The patented FlexiFOAM allows a continuous selection between wet and dry foam.

FAS CAFS-G10 allows an application with water-mist-function. Only this equipment allows the production of three extinguishing formats with variable dosage.

Certification: TUV – CE

