



FAS Diesel

High Pressure Fire Attack System Diesel Engine

DESCRIPTION ●

- Compact and lightweight portable system
- Working pressure up to 185 Bars – 2800 psi –
- Extension up to 120 meters hose length with no pressure loss
- Can be installed with our water tank or vehicle tank
- 4 Ergonomic handles to lift from all sides
- Stainless steel frames for longevity
- Easy training, intuitive use
- Discharge: Twin hose reels x 30 m, equipped with 2 twin lances for jet/spray / low/high pressure / foam
- Fast Connection type Safety Lock Guyson Fitting
- Water connection type Storz

OPERATING CONTROLS ●

Controls are easy to operate and include:

- Engine electric key start / stop
- Automatic throttle control
- Hour meter, Tachometer
- Pump pressure gauge
- Emergency Stop



SPECIFICATIONS & WARRANTY ●

Body and frame	Stainless Steel Grade 304
Pump	19 l/mn – 5 GPM
Maximum pressure	185 Bars – 2800 psi
Engine	10.9 CV – 8.0 Kw Lombardini
Diesel Tank	5 liters - 2 hours runtime at maximum speed
Battery	12V -30A/h Dry-cell sealed, 12 months load
Starter	12 volt electric key or Manual recoil
Hoses	2 hoses reel, length 2 x 30 m - extendable to 120 m
Weight / Dimensions	110 Kg / LxWxH 90x60x60
Guarantee	1 Year