



FAS H40

Fixed Fire Attack System Hydraulic Power

DESCRIPTION ●

- Modular system
- Working pressure up to 200 Bars – 3000 psi –
- No pressure loss up to 100 meters
- 2 Hose reels 100 m with power rewind
- Connected to vehicle water tank
- Powered with truck hydraulic system
- Stainless steel frames for longevity
- Easy training, intuitive use
- Discharge: Twin hose reels x 100 m, equipped with 2 x twin lance for jet/spray / low/high pressure / foam
- Foam inductor 0.1–3% (connected to vehicle foam tank)

OPERATING CONTROLS ●

Controls are easy to operate and include:

- Hydraulic valve start / stop,
- Pump pressure gauge,
- Emergency Stop.



SPECIFICATIONS & WARRANTY ●

Body and frame	Stainless Steel Grade 304
Pump	Speck triplex pump, Ceramic plunger
Maximum pressure	200 Bars – 3000 psi
Power	Hydraulic 24 kW
Flow rate	40 l/mn – 11 GPM
Starter	Solenoid Activation
Hoses	2 hoses reel, length 2 x 100 m – Power rewind
Weight	250 Kg
Dimensions (Unit)	LxWxH 500x280x300
Dimensions (Reels)	LxWxH 646x543x622
Guarantee	1 Year