



FAS Ultra S

High Pressure Fire Attack System Petrol Engine

DESCRIPTION ●

- Compact and lightweight portable system
- Working pressure up to 185 Bars – 2800 psi –
- Can be installed with our water tank or vehicle tank
- 4 Ergonomic handles to lift from all sides
- Stainless steel frames for longevity
- Easy training, intuitive use
- Discharge: 1 hose reel x 60 m, equipped with twin lance for jet/spray / low/high pressure / foam
- Fast Connection type Safety Lock Guyson Fitting
- Water connection type Storz

OPERATING CONTROLS ●

Controls are easy to operate and include:

- Engine electric key start / stop
- Automatic throttle control
- Hour meter, Tachometer
- Pump pressure gauge
- Emergency Stop



SPECIFICATIONS & WARRANTY ●

Body and frame	Stainless Steel Grade 304 Powder coated RED
Pump	Speck triplex pump, with Brass head and Ceramic pistons
Flow rate	19 l/mn – 5 GPM
Maximum pressure	185 Bars – 2800 psi
Engine	13 HP – 8.2 Kw Honda – 4 strokes
Petrol Tank	Integral 6 liters 1.5 hour runtime at maximum speed
Battery	12V –30A/h Dry-cell sealed, 12 months load
Starter	12 volt electric key or Manual recoil
Hose	1 hose reel, length 60 m
Weight	108 Kg
Dimensions	LxWxH 99x61x60
Guarantee	1 Year