

Fire Fly

High Pressure Fire Attack System Petrol Engine

DESCRIPTION



- Compact and Lightweight portable system
- Working Pressure up to 140 Bar 2100 psi
- Extension up to 90 meters hose length with no pressure loss
- · Can be installed with our water tank or vehicle tank
- Steel frame with epoxy coating
- · Easy training, intuitive use
- Discharge: 1 hose reel x 20 m or 30 m, equipped with 1 lance for jet-spray / low-high pressure for water
 - Fire Fly 20 & 30 : equipped with 1 lance for jet-spray high pressure for water .
 - Fire Fly 20F & 30F : equipped with 1 double lance for jet-spray low-high pressure for water / foam
- Fast connection type Safety Lock Guyson Fitting
- Water tank with Storz coupling

OPERATING CONTROLS

Controls are easy to operate and include:

SDECIEICATIONS & WADDANTY

- Manual choke control
- Pressure gauge
- Model F: Foam dosing system





SPECIFICATIONS & WARRANTY					
FIRE FLY	20	20F	30	30F	
Body and frame		Steel with epoxy black coating			
Pump		14 I/mn – 4 GPM			
Maximum pressure		140 Bars - 2100 psi			
Engine		6.4 CV - 4.6 Kw Honda - 4 strokes			
Petrol tank	3 litre	3 litres • 1.5 hour runtime at maximum speed			
Starter		Manual recoil			
Reel	1	1	1	1	
Hose	20 m	20 m	30 m	30 m	
Weight	48 kg	49 kg	52 kg	54 kg	
Dimensions (LxWxH)	55x6	55x60x60		55x60x66	
Warranty		1 year			