



FREEGEN

Synthetic Foam Concentrate FFF AR 3x3

Fluorine Free

PHYSICAL DATA ●

FREEGEN

Appearance / colour	off-white
Concentration of use on Hydrocarbons	3%
Concentration of use on Solvents	3%
Specific gravity at 20°C (Kg/dm ³)	1.04
Viscosity at 20°C (mPa.s)	
Brookfield LV, 60 rpm, spindle #4	1300
Cone and Plate, shear rate 375 s ⁻¹	145
pH at 20°C	7.5
Freezing point	-6°C
Sediments after ageing	0 %
Surface tension at 3% (mN/m)	25

FOAM QUALITY ●

Low Expansion	7
Drainage Time 25% / 50%	> 60 min
Medium Expansion	60
High expansion	400

Foam Expansion value depends on the equipment



PERFORMANCE & WARRANTY ●

FREEGEN meets international standards
EN 1568-1 & 2: Pass
EN1568-3: Class 1-A
EN1568-4: Class 1A - 1A
ICAO Level B
LASTFIRE
Marine: IMO

FREEGEN can be used with tap and sea water

FREEGEN can be used with all known equipment on the market.

FREEGEN has a 10 years warranty in its original packaging and at storage temperatures -30°C / +60°C