

GENEX B/R Fluorosynthetic Foam AFFF

PHYSICAL DATA •	GENEX B/R	
	1B	1R
Appearance liquid / Colour	Red	Orange
Concentration of use	1 - 3%	10 - 17%
Specific Gravity at 20°C (Kg/dm3)	1.04	1.08
Viscosity at 20°C (cStokes)	12	5
Freezing point	-22°C	-12°C
Ph at 20°C		8
Sediment after ageing	< 0.1%	
Surface tension (mN/m)	16	17
Interfacial tension (mN/m)	3	2

FOAM QUALITY

Low Expansion	8	10
Drainage time 25% / 50%	2 min/4 min	4 min/8 min

EXTINGUISHER - TYPICAL RATINGS

6 Litre	13A/21A/27A	144B/183B
9 Litre	27A/34A/43A	183B/233B



PERFORMANCE & WARRANTY

GENEX B/R meets international requirements EN 1568-3 ISO 7203-1 EN3 GENEX B/R contains corrosion inhibitors. GENEX B/R is designed to work effectively in extinguishers for B rating. GENEX B/R can be combined with PENTSPRAY to better the rating on A fires. GENEX B/R can be freeze protected with FREEZOL to protect up to -30°C.

GENEX B/R has a 5 years warranty in its original packaging and at storage temperatures -30°C/+60°C.

www.3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate, Corby, Northants, NN17 4JW, United Kingdom V.A.T. Registration No: 938 9418 70 Registred in England: 06236589