



HYFEX



Synthetic Foam Hi-Ex Fluorine Free

PERFORMANCE & WARRANTY

HYFEX meets international requirements
EN 1568-1 & 2: Pass
EN 1568-3: Class IIIC
ISO 7203-1, 2
Marine: BV

HYFEX is recommended for use in High Expansion applications.

HYFEX has a 10 years warranty in its original packaging and at storage temperatures 0°C / +60°C

PHYSICAL DATA

	HYFEX		
	1	3	6
Appearance /colour	Light yellow liquid		
Concentration of use	1 %	3 %	6 %
Specific Gravity at 20°C (Kg/dm3)	1.02	1.02	1.01
Viscosity at 20°C (cStokes)	12	5	4
Freezing point	-15°C	-5°C	-3°C
Ph at 20°C	7		
Sediments after ageing	< 0.1 %		
Surface tension (mN/m)	25		

FOAM QUALITY

Low Expansion	13		
Drainage Time 25% / 50%	8/16 min.		
Medium Expansion	120		
High Expansion	700	600	600

Foam Expansion values depend on the equipment



Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

No: FM 560021

www.3fff.co.uk