

PRO•FP•PROSEAL



FluoroProteinic Foam AR

● PERFORMANCE & WARRANTY

PRO and FP meets international requirements
EN 1568-3: Class III
Marine: BV (FP)

PROSEAL meets international requirements
EN 1568-3: Class IA
Marine: BV

PRO • FP • PROSEAL can be used with tap and sea water.

PRO • FP • PROSEAL has a 5 years warranty in its original packaging and at storage temperatures -30°C / +60°C.

● PHYSICAL DATA

| | PRO | | FP | | PROSEAL | |
|------------------------------------------------|-------------------|-------|-------|------|---------|-------|
| | 694 | 397 | 694 | 397 | 6 | 3 |
| Type | P | | FP | | FFFP | |
| Appearance / Colour | Dark brown Liquid | | | | | |
| Concentration of use | 6% | 3% | 6% | 3% | 6% | 3% |
| Specific Gravity at 20°C (Kg/dm ³) | 1.02 | 1.04 | 1.01 | 1.03 | 1.07 | 1.10 |
| Ph at 20°C | | | 7 | | | |
| Viscosity at 20°C (cStokes) | | | 5 | | | |
| Freezing point | -8°C | -12°C | -6°C | -6°C | -14°C | -14°C |
| Sediment after ageing | | | <0.5% | | | |
| Surface tension (mN/m) | | | 25 | 25 | 18 | 18 |
| Interfacial tension (mN/m) | | | | | 2 | 2 |

● FOAM QUALITY

| | | | | | | |
|--------------------------------|-----|-----|-----|-----|-----|-----|
| Low Expansion | 8 | 8 | 6 | 6 | 8 | 8 |
| Drainage time 25% / 50% (min.) | 3/6 | 3/6 | 2/4 | 2/4 | 3/6 | 3/6 |

Foam Expansion values depend on the equipment



No: FM 560021

Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

www.3fff.co.uk