

ATLANTICA D 3F

Portable Pump for Flooding Diesel engine

DESCRIPTION

- **Pump** Portable and compact
- **Max. Flow Rate** *Model A* : 600 GPM - 2300 l/mn
Model B : 475 GPM - 1800 l/mn
- **Structure** Stainless steel with handles
- **Priming** 7 meters in 20 seconds
- **Inlet / Outlet** *Model A* : Storz 4" - DN 100
Model B : Storz 3" - DN 70
- **Hoses** 1 of 5 m and 2 of 3 m 4" or 3" in transparent armed PVC
- **Weight** 87 Kgs
- **Blockage Free** takes solids up to a diameter 3" - DN80 - Can run dry
- **Option** Electrical start

SPECIFICATIONS & WARRANTY

- Pump housing made of seawater-proof aluminium alloy
- Impeller: patented, self-cleaning, aluminium-bronze alloy
- Sealing: Si-C to allow dry-run and endurance-run
- Engine: Hatz 1B27 5.4 HP / 4.0 kw
- Fuel tank: Diesel 3 L ; 2 hours autonomy at maximum speed
- Starter: Manuel recoil (electric starter option)
- Dimensions : 760x580x580
- Warranty 1 year



CE



Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

www.3fff.co.uk