

CHIEMSEE H

3F

Portable Pump for Liquids 90°C Electrical engine

DESCRIPTION

- **Pump** Portable and compact
- **Max. Flow Rate** *Model A* : 660 GPM - 2500 l/mn
Model B : 475 GPM - 1800 l/mn
- **Structure** Stainless steel with handles
- **Priming** 5 meters in 20 seconds
- **Inlet / Outlet** *Model A* : Storz 4" - DN 100
Model B : Storz 3" - DN 80
- **Sockets** Stainless Steel
1 flat 90° to suck down to floor level and
1 intake 120° to pump under water
- **Hoses** 2 of 5 m transparent 4" -DN100-
in PVC reinforced to 95°C
- **Weight** 53 Kgs
- **Blockage Free** takes solids up to a diameter 3"
– DN80 – Can run dry
Can pump liquids until 90°C

SPECIFICATIONS & WARRANTY

- Pump housing made of seawater-proof aluminium alloy
- Impeller: patented, self-cleaning, aluminium-bronze alloy
- Sealing: Si-C to allow dry-run and endurance-run
- Engine: Electrical 3.2 kw – 7.3 A ; Power 3P 400V / 50 Hz –
Phase inverter – Button ON/OFF
- Protection IP68
- Cable 20 meters, yellow, high resistance H07BQ-F-4G1.5 with
reinforced wire in stainless steel
- Warranty 1 year



CE



No: FM 560021

Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

www.3fff.co.uk