

D-300

3F

SF

Anti Foaming Agent Silicone Free Oil Free

PHYSICAL DATA

SF

Appearance / colour	Yellow liquid
Concentration of use	1%
Specific gravity at 20°C (Kg/dm ³)	0.99
Viscosity at 20°C (mPa.s)	230
Ph at 20°C (sol. 10%)	4
Freezing point	-6°C
Boiling point	> 190°C
Temperatures of use	0°C - +50°C
Surface tension at 1% (mN/m)	< 30

PERFORMANCE & WARRANTY

D-300 is an anti foaming agent based on fatty alkyl glycol ether, designed to break down fire fighting foams.

D-300 is silicone-free and oil-free. It does not leave a greasy residue after application.

D-300 has a long-lasting action and resists to mechanical stirring. It is therefore fully compatible with water treatment stations and does not interfere with the biomass.

D-300 is a ready-to-use product and is effective at 1%.

1. To avoid foam formation when releasing foam solution, we recommend inducing D-300 in the stream.
2. To treat existing foam, D-300 can be used in a high-pressure system. Our system FAS is recommended.

D-300 has a 1 year warranty in its original packaging and at storage temperatures 0°C / +40°C.



No: FM 560021

Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

www.3fff.co.uk