

FAS CAFS



Portable Back pack Foam Extinguishing System

DESCRIPTION

Model	FAS CAF G10	FAS CAF SF10
Volume		10 litres
Operating Pressure		18 bar
Flow rate		13,33 litre/min Wet 5,21 litre/min Dry
Operating temperature		0°C to 60°C
Distance of throw		16 metres Wet 11 metres Dry
Foam agent	GENEX ESC @3% by volume	FREDEX SF1 @100%
Frost protection	-10°C (FREEZOL @10%)	-5°C
Electrical test	EN3 – to 1,000 Volt / 2 metres distance	
Propellant	Air supplied by 300 bar cylinder (2 litre)	
Rating	55A – 233B or 43A – 183B (-10°C)	34A – 183B
Weight	12,5 kg empty - 28,8 kg filled	
Dimension	570 mm High - 220 mm Diameter	
Cylinder	CE 0036	

PERFORMANCE

High Performance for professional fire-fighters

This new addition to the FAS family of fire-fighting equipment from 3F combines quality, functionality and effectiveness for rapid and secure fire extinction. The unique high performance of the FAS CAFS is based on the alternate production of easy flowing wet foam or long lasting and sticky light foam providing rapid extinguishing with exceptional burn-back resistance.

FAS CAFS SF10 is eco-friendly and safe for the environment: it is **FLUORO-FREE** and **SOLVENT-FREE** thanks to our unique technology **Smart Foams®**

The patented *FlexiFOAM* allows a continuous selection between wet and dry foam.

FAS CAFS-G10 allows an application with water-mist-function. Only this equipment allows the production of three extinguishing formats with variable dosage.

Certification: TUV - CE



No: FM 560021

Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

www.3fff.co.uk