

Fire Flash

3F

High Pressure Fire Attack System Petrol Engine

DESCRIPTION

- Compact and Lightweight portable system For Quad
- Working Pressure up to 140 Bar – 2100 psi
- Extension up to 40 meters hose length with no pressure loss
- Can be installed with our water tank 70L – 19 Gal – or connected to our pump MX10
- Steel frame with epoxy coating, to be mounted in front of the Quad
- Easy training, intuitive use
- Discharge: 1 hose reel x 20 m, equipped with 1 lance for jet-spray / low-high pressure / foam
- Fast connection type Safety Lock Guyson Fitting
- The water tank includes a smaller foam tank of 8 Litres (2 gallons)

OPERATING CONTROLS

Controls are easy to operate and include:

- Manual choke control
- Pressure gauge
- Foam dosing system

SPECIFICATIONS & WARRANTY

Body and Frame	Steel with epoxy black coating
Pump	10 l/mn – 2.63 GPM
Maximum pressure	140 Bars - 2100 psi
Engine	5.5 CV - 3.6 Kw Loncin – 4 strokes
Petrol Tank	3.6 litres 2.5 hour runtime at maximum speed
Starter	Manual recoil
Hoses	1 hose reel, length 20 m – extendable to 40 m
Weight	50 Kg
Dimensions	LxWxH 100x25x40
Warranty	1 year



Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

No: FM 560021

www.3fff.co.uk