

## High Pressure Fire Attack System Petrol Engine

### SPECIFICATIONS & WARRANTY

Body and frame	Stainless Steel Grade 304
Pump	50 l/mn – 13 GPM
Maximum pressure	100 Bar – 1500 psi
Engine	20.8 HP - 15.5 Kw
Petrol Tank	8 liters 1.5 hour runtime at maximum speed
Battery	12V -30A/h Dry-cell sealed, 12 months load
Starter	12 volt electric key
Hoses	1 hose reel, length 1 x 60 m - extendable to 120 m
Weight	232 Kilo
Dimensions	LxWxH • 77cm x 64cm x 122cm
Guarantee	1 Year

### DESCRIPTION

- Compact vehicle or skid mounted system
- Working pressure 100 Bar – 1500 psi
- Extension up to 120 meters hose length with no pressure loss
- Can be installed with our water tank or vehicle tank
- Stainless steel frames for longevity
- Easy training, intuitive use
- Discharge: Single 60 metre hose supplied with quick release Jet and Cone nozzle
- Water connection type Storz

### OPERATING CONTROLS

*Controls are easy to operate and include:*

- Engine electric key start / stop
- Automatic throttle control
- Pump pressure gauge
- Emergency Stop
- Volt meter
- Fuel gauge
- Tiny tach – Engine revs
- Auto hose reel rewind
- Triton HP foam system



No: FM 560021

Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,  
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

[www.3fff.co.uk](http://www.3fff.co.uk)