

Fixed Fire Attack System Electric Drive

DESCRIPTION

- Modular system
- Working pressure up to 200 Bars – 3000 psi –
- No pressure loss up to 50 meters working height in buildings
- 1 to 12 Hose reels 30 m with spring recoil (1 per floor level)
- Connected to water tank in basement
- Electric Powered
- Stainless steel frames for longevity
- Easy training, intuitive use
- Discharge: 1 hose reel x 30 m per floor, equipped with 1 x twin lance for jet / spray / low / high pressure / foam
- Integrated foam tank and inductor 0.1-3% (option)

OPERATING CONTROLS

Controls are easy to operate and include:

- Automatic start / stop,
- Hour meter,
- Pump pressure gauge,
- Emergency Stop.

SPECIFICATIONS & WARRANTY

Body and frame	Stainless Steel Grade 304
Pump	Speck triplex pump, Ceramic plunger
Maximum pressure	200 Bars - 3000 psi
Power	Electric 11 kW 3ph 380-420V
Flow rate	20 l/mn – 5 GPM
Starter	Automatic switch
Hoses	1-12 hoses reels, length 30 m - Spring recoil
Weight	125 Kg (basement kit)
Dimensions (Unit)	LxWxH 100x60x50
Guarantee	1 Year

