

FREEDDEX SF 3F



Class A & B Extinguisher Additive Fluorine Free Solvent Free

PERFORMANCE & WARRANTY

FREEDDEX SF meets EN3 as a Class A & B water additive.

FREEDDEX SF must be used as a ready to use additive 100% active matter. The rating achieved under EN3 will be determined by the use of FREEDDEX SF1 or SF2.

FREEDDEX SF must be used at its best with our patented PTF system. PTF system is a tool to expand the foam prior to the discharge.

FREEDDEX SF has a 7 years warranty in its original packaging at storage temperatures 0°C / +60°C, and when contained in a lined extinguisher.

PHYSICAL DATA

	SF1	SF2	SF3
Colour		Pale yellow	
Specific Gravity at 20°C (Kg/dm ³)	1.02	1.01	1.04
Viscosity at 20°C (cStokes)	200	150	200
Freezing point		-5°C	-8°C
Ph at 20°C		7	8
Low expansion 100%		5	
Medium expansion			60
Drainage time 50%		>1 hour	>30'

EXTINGUISHER - Typical rating:

6 litre	21A - 113B 34B Acetone	21A - 113B	189B 27A
9 litre			



Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

www.3fff.co.uk