

HYDROFIGHTER^{3F}

Portable Fire Fighting Pump Petrol Engine

SPECIFICATIONS & GUARANTEE

Body, Head and Impeller	Marine Grade Aluminium EN 1706 AC-ALSi10MgSF Option: Copper alloy (Red Brass)
Wear Rings	Easy servicing Long Wearing UHMWPE
Shaft Seal	Spring loaded Mechanical Carbon-Ceramic for better withstanding if pump runs dry
Engine	Textron 2-Cylinder 4 Strokes 45kW with electronic injection
Fuel Tank	Integral 26 liters 2 hours runtime
Priming	Vacumat
Flow rate H10	1000 Lpm @ 10 Bars / 260 GPM @ 150 Psi
Flow rate H15	1500 Lpm @ 10 Bars / 400 GPM @ 150 Psi
Battery	12V
Starter	12 volt electric
Guarantee	1 Year
Certification	EN-14466

DESCRIPTION

- Compact portable centrifugal pump
- Dry weight: 169 kg – L1047 x W725 x H760 mm
- Inlet pressure up to 7 bars perfect for relay application
- Carry frame with double sided standard fixing points and 4 rotatable handles
- Option: Wheel set for 2 persons, easier handling
- Inlet: 1 x 4 ½ " (110mm) Storz – other coupling on request
- Outlet: 2 x 2 ½ " (70mm) Storz with pressure valve– other coupling on request
- Water cooled engine

OPERATING CONTROLS

Controls are easy to operate and include:

- Electrical starter start / stop,
- Throttle control,
- Starter battery / Hours run indicators,
- LED spotlight,
- Pump pressure control,
- Cover with illuminated color display and softkey buttons,
- Priming Vacumat,
- Discharge and intake pressure gauges,
- Drain cock,
- MagCode Plug Box for external charger



JHSTADT
Pumpen | Feuerlöschtechnik



No: FM 560021

Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

www.3fff.co.uk