




45 800
LUMENS

76 200
LUMENS

IP
65

131 000
LUMENS

IP
54



New

LUMAPHORE® LED XL

300 XL - 600 XL - 1000 XL



Advantages :

- Large and uniform lighting area
- Robust
- Compact
- Easy to deploy, to store and transport
- Low Power Consumption
- Work on generator or with the mains
- Light efficiency 150 Lm/watt
- LED technology : long life
- Immediate relighting



LUMAPHORE[®] LED XL



Electrical Specifications	300XL	600XL	1000XL
Total Lighting Output	300 W	520 W	910 W
Power of electricity supply	355 W	575 w	990 W

Safety Specifications	300XL	600XL	1000XL
Protection index	IP65 / IK10		IP54 / IK08
Wind resistance	162 Km/h		110 Km/h
Thermal protection	Yes		
Temperature range for use	-15°/+40°		

Photometric Specifications	300XL	600XL	1000XL
Area of illumination	2400 m ²	3200 m ²	4500m ²
Colour temperature	5000 °K		
total Lumens	45 800 lm	76200 lm	131 000 lm
Color rendering index	> 80		

Mechanical Specifications	300XL	600XL	1000XL
Diameter	22,5 cm		40 cm
Length	62 cm	91 cm	93 cm
Weight	5,1 Kg	7,7 Kg	15,2 Kg
Spigot type	Diameter 26 mm		
Optimal height for use	4 m		5 m
Average assembly time	2 mn		

Standard package	300XL	600XL	1000XL
Standard Flight-case	✓	✓	✓
power cable (Schuko plug)	7M	7M	11,4M
Ring of Suspension	✓	✓	X
IP65 Switch (ON/OFF - 180/360)	X	X	✓
Spigot (diam. 26mm)	✓	✓	✓

Options & Accessories	300XL	600XL	1000XL
additional power cable length	Option	Option	Option
Special plug (Marechal, IP67, IP68, ...)	Option	Option	Option
Switch ON/OFF IP65	Option	Option	Option
Switch 180/360° IP65	Option	Option	Option
Switch ON/OFF/180/360 IP65	Option	Option	✓
Flight-case IP67	Option	Option	X
Spigot (diam. , DIN, ...)	When ordering	When ordering	When ordering