

Mini CHIEMSEE 3F

Portable Pump for Flooding Electrical engine

DESCRIPTION

- **Pump** Portable and compact
- **Max. Flow Rate** *Model C700* : 700 l/mn - 185 GPM
Model B1000 : 1100 l/mn - 280 GPM
Model B1500 : 1500 l/mn - 400 GPM
- **Structure** Stainless steel with handles
- **Priming** 5 meters in 20 seconds
- **Inlet / Outlet** *Model C700* : C-Storz DN50 2"
Model B1000 : B-Storz DN70 3"
Model B1500 : B-Storz DN70 3"
- **PE sockets** 1 flat 90° to suck down to floor level and 1 intake 120° to pump under water
- **Hoses** 2 of 3 m 3" - DN80 - in transparent armed PVC
- **Weight** 39 Kgs
- **Blockage Free** takes solids up to a diameter 2½" – DN65 – Can run dry

SPECIFICATIONS & WARRANTY

- Pump housing made of seawater-proof aluminium alloy
- Impeller: patented, self-cleaning, aluminium-bronze alloy
- Sealing: Si-C to allow dry-run and endurance-run
- Engine: Electrical 2.7 kw – 15.1 A ; Power 1P 230V / 50 Hz – Button ON/OFF
- Protection IP68
- Cable 20 meters, yellow, high resistance H07BQ-F-4G1.5 with reinforced wire in stainless steel
- Warranty 1 year



CE



No: FM 560021

Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

www.3fff.co.uk