

OD 4000

3FF

Oil Dispersant

● PHYSICAL DATA

Appearance / Colour	Yellow liquid
Specific gravity at 15°C (Kg/dm ³)	0.93
Flash point	> +61°C
Pour point	< -20°C
Corrosion	No corrosive
Mixing	With tap or sea water

● PERFORMANCE & WARRANTY

OD4000 is a combination of surfactants and solvents.

OD4000 eliminates any oil spills on sea, lakes, rivers, ports, off-shore oil rigs, and on coast. It can also be used as a degreaser to clean contaminated tools and equipment.

DEFRA (UK), CEDRE (F), and SFT (N) certified OD4000 as a dispersing agent for Marine application for oil treatment.

OD4000 has proven low toxic on shrimps and is easily biodegradable.

● USE

OD4000 should be sprayed in an even manner over the spill. The emulsification process will start immediately and will transform oil into tiny droplets to stimulate bacteria degradation.

The rate of use depends strongly on the nature and the quantity of the spillage. For treatment of crude oil with limited thickness: 1:30 = 1 volume of OD4000 for 30 volumes of oil.

For treatment of heavy fuel and thick spills, the proportion should be increased to 1:10.

For spills over the coast or on rigs, OD4000 can be used at 3% in high-pressure systems.

OD4000 has a 2 years warranty in its original packaging and at storage temperatures -20°C/+50°C.



Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

No: FM 560021

www.3fff.co.uk