

STOPAL

3F

Vapour Suppressing Additive

● PERFORMANCE & WARRANTY

STOPAL should be applied at Medium Expansion at a minimum application of 10 l./m².mn. Foam blanket should be continuously renewed until spill control.

STOPAL should be used only with tap water.

STOPAL is suitable with all known equipment.

STOPAL has a 5 years warranty in its original packaging and at storage temperatures -30°C / +60°C.

● PHYSICAL DATA

Appearance / Colour	Yellow Gel
Concentration of use	6%
Specific Gravity at 20°C (Kg/dm ³)	1.05
Viscosity at 20°C (cStokes)	1600
Freezing point	-15°C
Ph at 20°C	7
Sediment after ageing	<0.1%
Surface tension (mN/m)	25

● FOAM QUALITY

Low Expansion	10
Drainage Time 25%	15 min.
Medium Expansion	80

Foam Expansion values depend on the equipment



No: FM 560021

Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

www.3fff.co.uk