



T-FOAM



Synthetic Training Foam Fluorine Free

PERFORMANCE & WARRANTY

T-FOAM can be used for all fire training, with tap water, sea water and brackish water.

T-FOAM has a 5 years warranty in its original packaging and at storage temperatures 0°C / +60°C.

PHYSICAL DATA

	T-FOAM	
	3	6
Appearance / Colour	Light yellow Liquid	
Concentration of use	3%	6%
Specific Gravity at 20°C (Kg/dm ³)	1.01	1.00
Ph at 20°C	7	
Viscosity at 20°C (cStokes)	5	2
Freezing point	-6°C	-3°C
Sediment after ageing	0%	
Surface tension (mN/m)	28	

FOAM QUALITY

Low Expansion	10	10
Drainage time 25% / 50%	6 min. / 10 min.	
Medium Expansion	50	50
High Expansion	400	400

Foam Expansion values depend on the equipment



No: FM 560021

Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

www.3fff.co.uk