

T-FOAM SF 3F

Synthetic Training Foam Fluorine Free Solvent Free

SF

PERFORMANCE & WARRANTY

T-FOAM SF can be used for all fire training, with tap water, sea water and brackish water.

T-FOAM SF has a 5 years warranty in its original packaging and at storage temperatures 0°C / +60°C.

PHYSICAL DATA

	T-FOAM SF		
	SF1 SF	SF3 SF	SF6 SF
Appearance / Colour	Light yellow Liquid		
Concentration of use	1%	3%	6%
Specific Gravity at 20°C (Kg/dm ³)	1.02	1.01	1.00
Ph at 20°C	7		
Viscosity at 20°C (cStokes)	25	5	2
Freezing point	-25°C	-10°C	-5°C
Sediment after ageing	0%		
Surface tension (mN/m)	28		

FOAM QUALITY

Low Expansion	12	12	12
Drainage time 25% / 50%	3 min. / 5 min.		
Medium Expansion	110	110	110
High Expansion	700	700	700

Foam Expansion values depend on the equipment



No: FM 560021

Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

www.3fff.co.uk