



Portable Pump for flooding Electrical engine

DESCRIPTION

Pump	Portable and compact to aspirate contaminated dirty water
Max. Flow Rate	200 GPM - 800 l/mn
Structure	Stainless steel with polyamide
Priming	In seconds in submersible position
Outlet	1 1/2" – DN40 –B-Storz coupling
Hose	5 m transparent 1 1/2" – DN40 in armed PVC
Weight	27 Kgs
Blockage Free	takes solids up to a diameter 1 1/2" – DN40 – Can run dry – No filter needed

SPECIFICATIONS & WARRANTY

- Pump housing made of seawater-proof aluminium alloy
- Impeller : patented, self-cleaning, aluminium-bronze alloy
- Sealing : Si-C to allow dry-run and endurance-run
- Engine : Electrical 1.8 kw – 9.7 A; Power 1P 230V / 50 Hz
- Protection IP68
- Cable 20 meters, yellow, high resistance H07BQ-F-4G1.5 with reinforced wire in stainless steel
- Warranty 1 year



Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589