



# FILMEX

## Fluorosynthetic Foam AFFF-AR

### FILMEX

#### PHYSICAL DATA ●

1x3 3x3 3x6

Appearance / colour	Yellow gel		
Concentration of use on Hydrocarbons	1%	3%	3%
Concentration of use on Solvents	3%	3%	6%
Specific Gravity at 20°C (Kg/dm <sup>3</sup> )	1.05	1.04	1.03
Viscosity at 20°C (mPa.s)	1600	1400	1200
Freezing point	-17°C	-15°C	-12°C
pH at 20°C	7		
Sediments after ageing	< 0.1 %		
Surface tension (mN/m)	20		
Interfacial tension (mN/m)	3		

#### FOAM QUALITY ●

Low Expansion	8
Drainage Time 25% / 50%	8 min. / 15 min.
Medium Expansion	50
High Expansion	400

Foam Expansion values depend on the equipment



#### PERFORMANCE & WARRANTY ●

FILMEX meets international requirements  
EN 1568-3: Class IA  
EN 1568-4: Class IA  
ISO 7203-1, 3  
NATO Listed

FILMEX can be used with tap and sea water.

FILMEX can be premixed for sprinklers, bladder tanks...

FILMEX has a 10 years warranty in its original packaging and at storage temperatures -30°C / +60°C