

3Fsmart Foam
SF

FREEGEN SF-LV

Synthetic Foam Concentrate

FFF AR 3x3

Fluorine Free

Solvent Free

PHYSICAL DATA ●

Appearance / colour	off-white
Concentration of use on Hydrocarbons	3%
Concentration of use on Solvents	3%
Concentration of use on Solids	1%
Specific gravity at 20°C (Kg/dm ³)	1.05
Viscosity at 20°C (mPa.s)	
Brookfield LV, 60 rpm, spindle #4	900
Cone and Plate, shear rate 375 s ⁻¹	90
pH at 20°C	7.5
Freezing point	-8°C
Sediments after ageing	0 %
Surface tension at 3% (mN/m)	25

FOAM QUALITY ●

Low Expansion	7
Drainage Time 25% / 50%	> 60 min
Medium Expansion	80
High expansion	400

Foam Expansion value depends on the equipment

SF: Smart Foam

FREEGEN SF-LV ● SF



PERFORMANCE & WARRANTY ●

FREEGEN SF-LV meets international standards
 EN 1568-1 & 2: Pass
 EN 1568-3: Class 1-A
 EN 1568-4: Class 1A - 1B
 ICAO Level B
 LASTFIRE
 Marine: IMO

FREEGEN SF-LV can be used with tap and sea water

FREEGEN SF-LV can be used for training at between 0.5 and 1.0

FREEGEN SF-LV can be used with all known equipment on the market.

FREEGEN SF-LV has a 10 years warranty in its original packaging and at storage temperatures -30°C / +60°C

www.3fff.co.uk
 info@3fff.co.uk
 Tel. +44 (0) 1536 202919

FRGNSFLV
 Version 4.3
 Revised November 2022

Unit B, 18 Brunel Road, Earlstree Industrial Estate,
 Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70
 Registered in England: 06236589