

3F

FREEGEN ULTRA

Synthetic Foam Concentrate

FFF AR 3x3

Fluorine Free

Solvent Free

PHYSICAL DATA ●

Appearance / colour	Off-white
Concentration of use on Hydrocarbons	3%
Concentration of use on Solvents	3%
Concentration of use on Solids	1%
Specific gravity at 20°C (Kg/dm ³)	1.06
Viscosity at 20°C (mPa.s)	
Brookfield LV, 60 rpm, spindle #4	1200
Cone and Plate, shear rate 375 s ⁻¹	140
pH at 20°C	7.5
Freezing point	-5°C
Sediments after ageing	0 %
Surface tension at 3% (mN/m)	28

FOAM QUALITY ●

Low Expansion	7
Drainage Time 25% / 50%	> 60 min
Medium Expansion	80
High expansion	400

Foam Expansion value depends on the equipment

SF: Smart Foam

FREEGEN ULTRA SF



PERFORMANCE & WARRANTY ●

FREEGEN ULTRA meets international requirements

EN 1568-1 & 2

EN 1568-3: Class 1-A (3%)

EN 1568-4: Class 1A-1A

ICAO Level B

LASTFIRE

Marine: IMO

FREEGEN ULTRA can be used with tap and sea water.

FREEGEN ULTRA can be premixed for sprinklers, bladder tanks...

FREEGEN ULTRA has a 10 years warranty in its original packaging and at storage temperatures -30°C / +60°C.

www.3fff.co.uk

info@3fff.co.uk

Tel. +44 (0) 1536 202919

FRGNULT

Version 2.0

Revised October 2023

Unit B, 18 Brunel Road, Earlstree Industrial Estate,
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70

Registered in England: 06236589